

Vortex Breakdown in Bioreactors

- BIFD 2011 -

Mohd-Zulhilmi P. Ismadi^{+,§}, Patrice Meunier[†], Andreas Fouras⁺ and Kerry Hourigan^{*+§},

⁺ Division of Biological Engineering and [§]Department of Mechanical and Aerospace Engineering,
Monash University, Melbourne, VIC3800, Australia

*Email: Kerry.Hourigan@eng.monash.edu.au, Web page:

<http://www.eng.monash.edu.au/bioeng/about/people/index.php?q=profile/hourigan>

[†] IRPHE, 49 av. Joliot-Curie, 13384 Marseille Cedex 13, France

Email: meunier@irphe.univ-mrs.fr, Web page: <http://www.irphe.fr/~meunier>

ABSTRACT

The flow inside a cylinder with a rotating end has been recently proposed as a suitable bioreactor for cells growth [1]. Indeed, it creates an efficient laminar mixing which is necessary for the homogenization of oxygen and nutrients, and for the removal of carbon dioxide. Moreover, the shear created by this flow is much smaller than in standard bioreactors which use a magnetic stirrer (rod, barrel or paddle). Finally, this flow is well known to lead to a vortex breakdown bubble [2], which could be beneficial to localise the cells and nutrients far from the boundaries. The properties and control of this flow are thus of critical importance for biological applications.

In this paper, we present experimental results on the control of vortex breakdown inside a cylinder with a rotating top lid. The vortex breakdown is controlled by injecting at the bottom a fluid with a small density difference. The density difference is obtained by mixing a heavy dye or alcohol to water in order to create a jet heavier or lighter than water. The injection of a heavy fluid creates a buoyancy force toward the bottom, which counteracts the recirculation in the cylinder and thus enhances the formation of a vortex breakdown bubble. The stability diagram shows that even a very small density difference of 0.02% is able to decrease by a factor of two the critical Reynolds number of appearance of the breakdown. On the other hand, the injection of a light fluid does not destroy the vortex breakdown. However, for large enough density differences (larger than 0.03%), the light fluid is able to pierce through the bubble and leads to a new structure of the vortex breakdown. Finally, a parallel is drawn between a light jet and a vortex ring generated at the bottom of the cylinder: strong vortex rings are able to pierce through the bubble whereas weak vortex rings are simply advected around the bubble [3].

In addition, the mixing efficiency of this flow has been studied quantitatively by measuring the temporal decay of the variance of the spatial dye distribution. The mixing time, required for homogenization of the dye, scales on the slow molecular diffusive time for a perfectly axisymmetric flow. However, the presence of a small tilt of the end plates breaks the symmetry and strongly accelerates the mixing. The mixing time scales on the convective time and can be a few orders of magnitude larger, even for small tilt angles.

REFERENCES

- [1] J. Dusting, J. Sheridan and K. Hourigan, "A fluid dynamics approach to bioreactor design for cell and tissue culture", *Biotechnology and Bioengineering*, Vol. **94**, pp.1196–1208, (2006).
- [2] M. P. Escudier, "Observations of the flow produced in a cylindrical container by a rotating endwall", *Exp. Fluids*, pp. 189-196, (1984).
- [3] M. P. Ismadi, P. Meunier, A. Fouras and K. Hourigan, "Experimental control of vortex breakdown by density effects", *to appear in Phys. Fluids*, (2011).