

# Application of a Microstructured Brittle Damage Model to laboratory Tests on Rocks

F. Calidonna<sup>1</sup>, M. L. De Bellis<sup>2</sup>, G. Della Vecchia<sup>1</sup>, M. Ortiz<sup>3</sup> and A. Pandolfi<sup>1</sup>

<sup>1</sup> Civil and Environmental Engineering Department  
Politecnico di Milano  
Piazza Leonardo da Vinci 32, 20133 Milano, Italy  
fabrizio.calidonna@mail.polimi.it, gabriele.dellavecchia@polimi.it, anna.pandolfi@polimi.it

<sup>2</sup> Department of Engineering and Geology  
University of Pescara-Chieti  
Viale Pindaro 42, 65127 Pescara, Italy  
marialaura.debellis@unisalento.it

<sup>3</sup> Engineering and Applied Sciences Division, CALTECH  
1200 California Blvd, Pasadena CA, USA  
Mathematical Institute, Bonn University  
Endenicher Allee 60, D-53115 Bonn, Germany  
ortiz@aero.caltech.edu

## ABSTRACT

A multiscale brittle damage model is used to simulate the behavior of confined rock materials in laboratory tests. The material model is characterized by microstructures in the form of recursive equidistant parallel cohesive/frictional faults, and it is defined by a reduced number (seven) of material constants. Simulations show that the model is able to capture several important features observed in rocks, in particular the reduction of the overall stiffness for increasing deterioration of the material, fragile to ductile transition, strain localization, shear band formation, and more general size-effect. The model is applied to the simulation of the behavior of the rocks at the material point scale and at the laboratory scale as a boundary value problem. The model shows good predictive properties for a large number of geo-materials, in particular it is able to establish a correspondence between the actual microstructure and the macroscopic geometry of shear bands. Specifically, simulations at the full scale are able to model strain localization with the formation of single or multiple shear bands.

## REFERENCES

- [1] Pandolfi A., Conti S., Ortiz M. “A recursive-faulting model of distributed damage in confined brittle materials”. *Journal of the Mechanics and Physics of Solids*, Vol. 54, 1972-2003, 2006.
- [2] De Bellis ML, Della Vecchia G., Ortiz M., and Pandolfi A. “A linearized porous brittle damage material model with distributed frictional-cohesive faults”. *Engineering Geology*, Vol. 215, 10-24, 2016.
- [3] De Bellis ML, Della Vecchia G, Ortiz M, Pandolfi A. “A multiscale model of distributed fracture and permeability in solids in all-round compression”, *Journal of the Mechanics and Physics of Solids*, Vol. 104 21-31, 2017.