

COMPOSITES MODELLING: CHARACTERIZATION, BEHAVIOUR AND STRUCTURES

LUIS A. TÁVARA, VLADISLAV MANTIČ

Grupo de Elasticidad y Resistencia de Materiales
ETSI, Universidad de Sevilla, Camino de los Descubrimientos s/n, Sevilla, 41092
ltavara@us.es, mantic@us.es, www.germus.es

Key words: Composites, behaviour, characterization, damage.

ABSTRACT

At present, composite materials (especially carbon and glass fibre-reinforced polymers, CFRPs and GFRPs) are extensively used in a wide range of engineering applications. Thus, there exists an increasing demand for developing computational tools to obtain properties and study behaviour of composite material systems [1-4].

From the mechanical point of view, diverse damage mechanisms may affect the performance of such composites. These characteristic damage scenarios are generally categorized as: (i) intralaminar damage events, e.g. fibre fracture, matrix failure, fibre-matrix decohesion, among others, and (ii) interlaminar failure, i.e. delamination, or debonding between adhesively bonded entities in engineering applications [5-8]. Thus, predictive modelling tools allowing the accurate prediction of distinct failure scenarios in fibre-reinforced polymer composites (FRPCs) are desirable.

It is also noticeable that the use of composites in primary structures has gained a great relevance in the last years [9]. Thus, the aim of the thematic session is to share the latest developments on numerical tools used to model composites. Applications of existing tools regarding the characterization and behaviour of composites and composite structures are also welcome.

REFERENCES

- [1] Q.S. Yang, Q.H. Qin, “Modelling the effective elasto-plastic properties of unidirectional composites reinforced by fibre bundles under transverse tension and shear loading” *Mater Sci Eng A*, 344: 140–145 (2003).
- [2] S.G. Mogilevskaya, S.L. Crouch “A Galerkin boundary integral method for multiple circular elastic inclusions with uniform interphase layers”, *Int J Solids Struct*, 41: 1285–1311 (2004).
- [3] A. Carpinteri, M. Paggi, G. Zavarise, “Snap-back instability in micro-structured composites and its connection with superplasticity”, *Strength Fract Complexity*, 3: 61–72 (2005).

- [4] C. González, J. Llorca, “Mechanical behavior of unidirectional fiber-reinforced polymers under transverse compression: microscopic mechanisms and modeling”, *Compos Sci Technol*, 67: 2795–2806 (2007).
- [5] J. Varna, L.A. Berglund, M.L. Ericson, “Transverse single fiber test for interfacial debonding in composites 2: modelling” *Composites Part A*, 28: 317–326 (1997).
- [6] F. París, E. Correa, J. Cañas. “Micromechanical view of failure of the matrix in fibrous composite materials”, *Compos Sci Technol*, 63, 1041–1052 (2003).
- [7] A. Turón, P.P. Camanho, J. Costa, C.G. Dávila, “A damage model for the simulation of delamination in advanced composites under variable-mode loading” *Mech Mater*, 38: 1072–1089 (2006).
- [8] L. Távara, V. Mantic, E. Graciani and F. París, “Modelling interfacial debonds in unidirectional fibre-reinforced composites under biaxial transverse loads”, *Composite Structures*, 136: 305-312 (2016).
- [9] J. Reinoso, A. Blázquez, L. Távara, F. París, C. Arellano. “Damage tolerance of composite runout panels under tensile loading”, *Composites Part B: Engineering*, 96:79–93 (2016).