

## CRACK-PARTICLE INTERACTIONS IN HETEROGENEOUS MATERIALS

Sathiskumar A Ponnusami\* and Sergio Turteltaub

Faculty of Aerospace Engineering  
Delft University of Technology  
Postbus 5058, 2600 GB Delft, The Netherlands  
{S.AnusuyaPonnusami, S.R.Turteltaub}@tudelft.nl

**Key Words:** *Crack-particle interactions, cohesive elements, fracture mechanics, heterogeneous materials*

Particles are typically embedded in a matrix material to increase its functionality, particularly its effective fracture behavior. A classic example is a particle-reinforced material where crack shielding and deflection lead to toughening of the original material. More recently, however, a distinct mechanism using embedded particles has been proposed to enhance the resistance against cracking. In particular, in the so-called self-healing materials, particles containing a suitable healing agent are dispersed in the matrix. Upon loading the material, existing microcracks interact with the healing particles, thereby activating the self-healing mechanism. In order to successfully trigger the healing mechanism, it needs to be ensured that a propagating crack gets attracted towards the healing particles instead of deflected away from them. In addition, the crack needs to break the healing particles, which requires a sufficiently strong particle-matrix interface. Consequently, the crack-particle interaction is a critical issue that needs to be addressed in order to facilitate the successful development of self-healing materials [1].

In this work, crack-particle interaction in a two-phase material system has been analyzed. It involves understanding how cracks interact with constituent phases in the heterogeneous system. As a first step, a system with a single particle embedded in a ceramic matrix is considered. Finite element simulations are performed to investigate the effect of properties of particle, matrix and interface on the crack propagation. Cohesive elements based on traction-separation laws are used to simulate fracture in the two-phase system. A parametric analysis has been carried out to identify the favorable range of elastic and fracture properties for the healing particles and the ceramic matrix. Subsequently, the crack interaction with arrays of particles has been addressed. Structured and randomly distributed arrays of particles are considered for the study. A general design guideline is provided for selecting the healing particles in terms of their mechanical properties.

### REFERENCES

- [1] Z. Derelioglu, Sathiskumar. A. Ponnusami, S. Turteltaub, S. van der Zwaag and W.G. Sloof, Healing Particles in Self-Healing Thermal Barrier Coatings, Fourth International Conference on Self-Healing Materials ICSHM2013, Ghent, Belgium, 2013