

A new framework for curving structured boundary-layer meshes

ADMOS 2019

A. Johnen¹, X. Roca², T. Toulorge³ and J.-F. Remacle¹

¹ Université catholique de Louvain, Louvain-la-Neuve, Belgium

² Barcelona Supercomputing Center, Barcelona, Spain

³ Cenaero, Gosselies, Belgium

ABSTRACT

We propose a new framework for curving any structured boundary-layer (BL) mesh (that we define as a BL mesh constructed by extruding the boundary and splitting the created elements if simplicial elements are requested). Similarly to the method of [1], we curve each stack of elements separately. However, we allow the surface between the BL and the external mesh to be curved which is useful to control the thickness of the first layers. We make the choice to fix the corner of BL elements and we impose the mapping of the elements to be linear in the direction of extrusion. We first compute a curving of the exterior surface such that the distance to the boundary is constant in the least-square sense. This curving induce a deformation that can break the validity or significantly decrease the quality of the external mesh [2, 3]. When it is the case, the deformation is reduced such that to recover the validity and quality of the external mesh. The interior of the BL is then curved by using a linear transfinite interpolation or by solving an elliptic problem. In 3D, interfaces between stacks are curved before curving the stacks which ensures a better parallelization of the whole process. In order to better control the thickness of the first layers, we compute the curving of the first layer surface in the same way we compute the curvature of the exterior surface and use this information for doing a Hermite transfinite interpolation. In pathologic cases, this can produce invalid elements in the stack in which case we compute a combination of the linear and Hermite transfinite interpolation. This method is extremely fast, produce high-quality curved BL mesh and is able to handle complex BL mesh. While not fully robust, an *a posteriori* optimization process allows to recover invalid stacks.

Acknowledgement

A. Johnen is mandated by the Belgian Fund for Scientific Research (F.R.S.-FNRS).

REFERENCES

- [1] D. Moxey, M. Green, S. Sherwin, J. Peiró, An isoparametric approach to high-order curvilinear boundary-layer meshing, *Computer Methods in Applied Mechanics and Engineering* 283 (2015) 636–650.
- [2] A. Johnen, J.-F. Remacle, C. Geuzaine, Geometrical validity of curvilinear finite elements, *Journal of Computational Physics* 233 (2013) 359–372.
- [3] A. Johnen, C. Geuzaine, T. Toulorge, J.-F. Remacle, Efficient computation of the minimum of shape quality measures on curvilinear finite elements, *Procedia Engineering* 163 (2016) 328–339.