

USING A REDUCED SET OF FOURIER MODES IN TERMS OF A FFT-BASED MICROSTRUCTURE SIMULATION

Christian Gierden^{1,*}, Johanna Waimann¹, Bob Svendsen^{2,3} and Stefanie Reese¹

¹ Institute of Applied Mechanics, RWTH Aachen University, Mies-van-der-Rohe-Straße 1, D-52074 Aachen, Germany,

{christian.gierden, johanna.waimann, stefanie.reese}@rwth-aachen.de

² Material Mechanics, RWTH Aachen University, Schinkelstraße 2, D-52062 Aachen

³ Microstructure Physics and Alloy Design, Max-Planck-Institut für Eisenforschung GmbH, Max-Planck-Straße 1, D-40237 Düsseldorf, Germany, b.svendsen@mpie.de

Keywords: *Microstructure simulation, FFT, Spectral solver, Model order reduction*

Given a heterogeneous material, the mechanical behavior of its microstructure can be investigated by an algorithm that uses the Fourier representation of the Lippmann-Schwinger equation [1]. Incorporating a model order reduction technique based on calculations with a reduced set of Fourier modes, the computational cost of this algorithm can be decreased [2]. It was shown that the accuracy of this model order reduction technique strongly depends on the choice of Fourier modes [3] by considering a geometrically adapted rather than a fixed sampling pattern to define the reduced set of Fourier modes. Since it is difficult to define a geometrically adapted sampling pattern for complex microstructures, we additionally introduced a strain-based sampling pattern [4]. The accuracy and adaptability of this strain-based reduced set of Fourier modes is shown by incorporating composite and polycrystalline microstructures, respectively.

REFERENCES

- [1] H. Moulinec and P. Suquet, A numerical method for computing the overall response of nonlinear composites with complex microstructure. *Comput. Methods Appl. Mech. Eng.*, Vol. **157**(1–2), pp. 69-94, 1998.
- [2] J. Kochmann, K. Manjunatha, C. Gierden, S. Wulfinghoff, B. Svendsen and S. Reese, A simple and flexible model order reduction method for FFT-based homogenization problems using a sparse sampling technique. *Comput. Methods Appl. Mech. Eng.*, Vol. **347**, pp. 622–638, 2019.
- [3] C. Gierden, J. Waimann, B. Svendsen and S. Reese, A geometrically adapted reduced set of frequencies for a FFT-based microstructure simulation. *Comput. Methods Appl. Mech. Eng.*, Vol. **386**, 114131, 2021.
- [4] C. Gierden, J. Waimann, B. Svendsen and S. Reese, FFT-based simulation using a reduced set of frequencies adapted to the underlying microstructure. *Comput. Methods Mater. Sci.*, Vol. **21**(1), pp. 51–58, 2021.