

HYBRID FINITE-VOLUME/DISCONTINUOUS GALERKIN FRAMEWORK FOR THE SOLUTION OF MULTIPHYSICS PROBLEMS USING UNSTRUCTURED MESHES

Vadim Maltsev¹, Panagiotis Tsoutsanis¹, Martin Skote¹

¹ Cranfield University, Cranfield MK43 0AL, United Kingdom,
v.maltsev@cranfield.ac.uk, panagiotis.tsoutsanis@cranfield.ac.uk,
m.skote@cranfield.ac.uk

Keywords: *Multiphysics Problems, Diffuse-Interface Method, Hybrid Finite-Volume /Discontinuous Galerkin framework*

A hybrid FV/DG framework is developed for the simulation of compressible multi-species flows on unstructured meshes with a five-equation Diffuse-Interface Model [1]. The high order DG method is employed for the purpose of limiting the material interface smearing typical of the diffuse-interface models resulting from excessive numerical dissipation [3, 4].

In order to ensure high-order accuracy in smooth flow regions and non-oscillatory behaviour near shocks or material interfaces, the hybrid scheme resorts to the underlying FV method when invalid cells are detected by a troubled cell indicator checking the unlimited DG, and enables a high-order non-linear CWENOZ reconstruction [8, 6] if the solution present oscillations. The CWENO and CWENOZ type reconstruction uses a high-order polynomial for the central stencil and a lower-order polynomial for the directional stencils enhancing robustness and efficiency of classic WENO schemes.

To achieve consistency in advecting material interfaces at constant pressure and velocity, the source term from the non-conservative equation is discretised compatibly with the Riemann solver, following the work of Johnsen and Colonius [9]. The results presented are obtained with the UCNS3D open-source CFD code [5, 6, 7].

REFERENCES

- [1] G.Allaire, S.Clerc, S.Kokh, *A Five-Equation Model for the Simulation of Interfaces between Compressible Fluids*, Journal of Computational Physics, 181 (2002)
- [2] P.Tsoutsanis, E.M.Adebayo, A.C.Merino, A.P.Arjona, M.Skote, *CWENO Finite-Volume Interface Capturing Schemes for Multicomponent Flows Using Unstructured Meshes*, Journal of Scientific Computing, 89:64, 2021.
- [3] R.Saurel, C.Pantano, *Diffuse-Interface Capturing Methods for Compressible Two-Phase Flows*, Annu. Rev. Fluid Mech. 50 (2018).
- [4] V.Maltsev, M.Skote, P.Tsoutsanis, *High-order methods for diffuse-interface models in compressible multi-medium flows: A review*, Phys. Fluids 34(2022).
- [5] P.Farmakis, X.Nogueira, P.Tsoutsanis, *WENO for unstructured meshes using a relaxed a posteriori MOOD limiting approach*, Computer Methods in Applied Mechanics and Engineering, V363 112921, 2020.
- [6] P.Tsoutsanis, M.Dumbser, *Arbitrary high-order central non-oscillatory schemes on mixed-element unstructured meshes*, Computer and Fluids, V225 104961, 2021.
- [7] P.Tsoutsanis, *Stencil selection algorithm for WENO schemes on unstructured meshes*, Journal of Computational Physics, p.69-94, 2018.
- [8] R.Borges, M.Carmona, B. Costa, W.S.Don, *An improved weighted essentially non-oscillatory scheme for hyperbolic conservation laws*, Journal of Computational Physics 227 (2008).
- [9] E.Johnsen, T.Colonius, *Implementation of WENO schemes incompressible multicomponent flow problems* Journal of Computational Physics 219 (2006).