

A Mixed Finite Element Formulation for Arbitrary Element Geometries and Nearly-Incompressible Finite Elasticity

Bjorn Sauren^{*1}, Simon Klarmann¹ and Sven Klinkel¹

¹ Chair of Structural Analysis and Dynamics, RWTH Aachen University,
Mies-van-der-Rohe-Str. 1, 52062 Aachen, Germany. sauren@lbb.rwth-aachen.de,
www.lbb.rwth-aachen.de

Keywords: *scaled-boundary, mixed formulation, finite elasticity, volumetric locking*

In this work, the displacement-based scaled-boundary finite element method (SBFEM) is extended to a mixed displacement-pressure formulation for both the geometrically and materially nonlinear analysis of nearly-incompressible solids. The displacements and pressures are both parameterized by a scaled-boundary approach, for which an interpolation in scaling direction is used. Here, higher-order interpolation functions may be employed. It is shown that by introducing the pressure as a field variable, the occurrence of volumetric locking is no longer dependent on the location of the scaling center. This allows for a scaling center at arbitrary locations, both inside and outside the element domain. Other than that, the formulation is valid for non-star-convex element geometries. Numerical examples show that the method is capable of alleviating volumetric locking for arbitrary polygonal meshes and is beneficial in comparison to the displacement-based method when it comes to modeling nearly-incompressible materials.

REFERENCES

- [1] S. Klinkel and R. Reichel, A finite element formulation in boundary representation for the analysis of nonlinear problems in solid mechanics. *Comput. Methods Appl. Mech. Engrg.*, Vol. **347**, pp. 295–315, 2019.
- [2] U. Brink and E. Stein, On some mixed finite element methods for incompressible and nearly incompressible finite elasticity. *Comput. Mech.*, Vol. **19**, pp. 105–119, 1996.