

Simulation of the flow-acoustic-structural interaction in flow ducts using a partitioned approach in the time domain

Jurgen Kersschot^{1,2}, Hervé Denayer^{1,2}, Wim De Roeck¹ and Wim Desmet^{1,2}

¹ Dept. of Mechanical Engineering, KU Leuven, Celestijnenlaan 300, 3001 Leuven, Belgium, jurgen.kersschot@kuleuven.be

² DMMS Lab, Flanders Make, 3001 Leuven, Belgium

Keywords: *Partitioned simulation approach, Flow-acoustic-structural interaction*

Duct systems confining a subsonic air flow, such as ventilation ducts, often have a lightweight design. These lightweight constructions are easily excited by unsteady pressure fluctuations in the flow, causing structural vibrations and noise emissions. Designing effective solutions for this problem requires a better understanding of the multi-physical interaction and efficient modelling tools. For modelling the convective effects influencing the noise propagation in the flow-acoustic domain, it suffices to solve the linearized Navier-Stokes equations, describing the propagation of first-order fluctuations through a known and steady mean flow. The structural domain can be described by the Mindlin-Reissner shell theory. Due to the confined configuration, the vibro-acoustic interaction is a strong two-way interaction and is included in the model by coupling a flow-acoustic solver with a structural solver. The kinematic and dynamic continuity at the interface is ensured in this partitioned approach by a data exchange during runtime between the solvers.

This partitioned simulation approach is used to study the flow-acoustic-structural interaction for different flow configurations. The flow-acoustic solver solves the time domain Linearized Euler Equations and uses a higher-order discontinuous Galerkin method for the spatial discretization and an explicit Runge-Kutta scheme for time marching. The structural solver for linear elasto-dynamics applies the Finite Element method and the implicit Newmark-Beta scheme. The data exchange is carried out using the Conventional Serial Staggered scheme and the Nearest Projection mapping algorithm of the open-source library preCICE [1]. The analysis of the flow-acoustic-structural interaction in a flexible flow duct with rectangular cross section was given in [2]. In this work, also the energy conservation during the data exchange between the two physical domains will be verified.

REFERENCES

- [1] H.-J. Bungartz and F. Lindner et al., preCICE—a fully parallel library for multi-physics surface coupling. *Computers & Fluids*, Vol. **141**, pp. 250–258, 2016.
- [2] J. Kersschot and H. Denayer et al., Simulation of the Vibro-acoustic Interaction in a Flexible Flow Duct Using a Partitioned Approach in the Time Domain. *AIAA AVIATION 2021 FORUM*, p. 2148, 2021.