

# MULTIGRID ALGORITHMS FOR *HP*-DISCONTINUOUS GALERKIN DISCRETIZATIONS OF ELLIPTIC PROBLEMS

Paola F. Antonietti<sup>1</sup>, Marco Sarti<sup>2</sup> and Marco Verani<sup>3</sup>

<sup>1</sup> MOX, Dipartimento di Matematica, Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133, Milano, Italy. [paola.antonietti@polimi.it](mailto:paola.antonietti@polimi.it)

<sup>2</sup> MOX, Dipartimento di Matematica, Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133, Milano, Italy. [marco.sarti@polimi.it](mailto:marco.sarti@polimi.it)

<sup>3</sup> MOX, Dipartimento di Matematica, Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133, Milano, Italy. [marco.verani@polimi.it](mailto:marco.verani@polimi.it)

**Key words:** *hp-version discontinuous Galerkin, multigrid algorithms.*

We present W-cycle multigrid algorithms for the solution of the linear system of equations arising from a wide class of *hp*-version discontinuous Galerkin discretizations of elliptic problems. Starting from a classical framework in multigrid analysis, we define a smoothing and an approximation property, which are used to prove the uniform convergence of the W-cycle scheme with respect to the granularity of the grid and the number of levels. The dependence of the convergence rate on the polynomial approximation degree  $p$  is also tracked, showing that the contraction factor of the scheme deteriorates with increasing  $p$ . A discussion on the effects of employing inherited or non-inherited sublevel solvers is also presented. Numerical experiments confirm the theoretical results.